

MS28 - 21 sqm

Mobile LED Screen



Safety

All our Mobile LED Screens

- are approved by Dansk Teknologisk Institut and Alvelid Engineering to be used up to wind speeds of 17,2 m/s
- have multiple safety lock systems for the hydraulic system
- are equipped with dual video processors as a back-up system

Add ons

Please contact us for further information about Digital Banners, Info Channels etc.

Technical Specifications

Screen	
Display size:	21 m ²
Display dimensions:	W: 6000 H: 3500 mm
Display resolution:	W: 1152 H: 672 px
Picture format:	16:9
Pixell pitch:	5,2 mm
Brightness:	> 5000 nits
Viewing angle:	H: 120° V: 60°
Screen rotation:	360°
Min. rotation space from trailer body (each side):	1943 mm
Input signals:	CVBS, 3G-SDI, DVI, HDMI, VGA
Trailer	
Trailer dimensions:	L: 7900 W: 2170 H: 3000 mm
Trim height:	3000 - 3250 mm
Weight:	3500 kg
Built in studio:	No
Built in generator:	No
External power connector:	32 A, 3 phase, 400V, CEE
Power consumption (max):	17 A
External generator (without earth fault breaker):	15,6 kVA
Truck & Trailer	
Length, total:	13860 mm
Weight, total:	5750 kg

inter.aktiv
- Professionelle AV-løsninger

Grønlandsvej 2 · 5700 Svendborg · Telefon 2260 6014
kontakt@inter-aktiv.dk · **www.inter-aktiv.dk**